



ADAIR® LIMESTONE  
 MASONRY UNIT,  
 MIN. 1" AIR SPACE,  
 RIGID OR SEMI-RIGID  
 INSULATION (THICKNESS  
 DEPENDANT ON REQUIRED  
 R-VALUE),  
 AIR/VAPOR BARRIER  
 MEMBRANE,  
 CONCRETE MASONRY UNIT (CMU),  
 METAL FURRING (OPTIONAL),  
 GYPSUM WALLBOARD.

MORTAR DROP  
 CONTROL

FLASHING MEMBRANE  
 SURFACE ADHERE  
 TO SUBSTRATE

UNOBSTRUCTED  
 WEEP SYSTEM  
 @ 24" O/C

PREFINISHED METAL  
 DRIP EDGE SET ON  
 TWO BEADS OF SEALANT  
 PARGING

HORIZONTAL  
 REINFORCING  
 WHEN REQUIRED

VERTICAL  
 REINFORCING  
 IF REQUIRED

COMPRESSIBLE  
 BACKER ROD  
 AND SEALANT

FLOOR BY OTHER

3/8 MIN.  
 6" MIN.  
 COMPRESSIBLE BACKER  
 ROD AND SEALANT  
 PREMOLDED EXPANSION  
 JOINT FILLER  
 2% SLOPE MIN.

BUILDING PAPER  
 AIR/VAPOR BARRIER  
 STEEL STUD  
 FURRING WITH  
 INSULATION



**ARRISCRAFT**  
 INTERNATIONAL  
 BUILDING STONE • BRICK • LIMESTONE

**ARRISCRAFT • CADD**

TITLE:  
**FOUNDATION TO WALL  
 JUNCTION AND PAVING**

DATE DRAWN:  
 08/30/04

SCALE:  
 3"=1'-0"

DRAWN BY:  
 LPS

DETAIL No:  
 CB AD04S

**U001**