

ADAIR® LIMESTONE
 MASONRY UNIT,
 MIN. 1" AIR SPACE,
 RIGID OR SEMI-RIGID
 INSULATION (THICKNESS
 DEPENDANT ON REQUIRED
 R-VALUE),
 AIR/VAPOR BARRIER
 MEMBRANE,
 CONCRETE MASONRY UNIT (CMU),
 METAL FURRING (OPTIONAL),
 GYPSUM WALLBOARD.

HORIZONTAL
 REINFORCING
 WHEN REQUIRED

VERTICAL
 REINFORCING
 IF REQUIRED

FLOOR BY OTHER

MORTAR DROP
 CONTROL

FLASHING MEMBRANE
 SURFACE ADHERE
 TO SUBSTRATE

UNOBSTRUCTED
 WEEP SYSTEM
 @ 24" O/C

PREFINISHED METAL
 DRIP EDGE SET ON
 TWO BEADS OF SEALANT

3/8 MIN.

6" MIN.

PARGING

BUILDING PAPER

STEEL STUD
 FURRING WITH
 INSULATION

GYPSUM
 WALLBOARD

AIR/VAPOR BARRIER



ARRISCRAFT
 INTERNATIONAL
 BUILDING STONE • BRICK • LIMESTONE

ARRISCRAFT • CADD

TITLE:

ALTERNATIVE FOUNDATION TO WALL
 JUNCTION AND SOIL

DATE DRAWN:

08/30/04

SCALE:

3"=1'-0"

DRAWN BY:

LPS

DETAIL No:

CB AD04S

U002