

ADJUSTABLE WALL TIE
INSULATION RETAINER

ADAIR® LIMESTONE MASONRY UNIT, MIN. 1" AIR SPACE, RIGID OR SEMI-RIGID INSULATION (THICKNESS DEPENDANT ON REQUIRED R-VALUE), AIR/VAPOR BARRIER MEMBRANE, CONCRETE MASONRY UNIT (CMU), METAL FURRING (OPTIONAL), GYPSUM WALLBOARD.

HORIZONTAL REINFORCING WHEN REQUIRED
VERTICAL REINFORCING IF REQUIRED

FLOOR BY OTHER

MORTAR DROP CONTROL
FLASHING MEMBRANE SURFACE ADHERE TO SUBSTRATE
UNOBSTRUCTED WEEP SYSTEM @ 24" O/C
PREFINISHED METAL DRIP EDGE SET ON TWO BEADS OF SEALANT
HIGH SLUMP MASONRY GROUT
PROTECTION BOARD

BUILDING PAPER
AIR/VAPOR BARRIER



ARRISCRAFT
INTERNATIONAL
BUILDING STONE • BRICK • LIMESTONE

ARRISCRAFT • CADD

TITLE: FOUNDATION WALL/
BURIED MASONRY UNIT
(PROTECTION BOARD)

DATE DRAWN:
08/30/04

SCALE:
3"=1'-0"

DRAWN BY:
LPS

DETAIL No:
CB AD04S

U004