



ADAIR® LIMESTONE MASONRY UNIT, MIN. 1" AIR SPACE, RIGID OR SEMI-RIGID INSULATION (THICKNESS DEPENDANT ON REQUIRED R-VALUE), AIR/VAPOR BARRIER MEMBRANE, CONCRETE MASONRY UNIT (CMU), METAL FURRING (OPTIONAL), GYPSUM WALLBOARD.

VERTICAL REINFORCING IF REQUIRED

FLOOR BY OTHER

ADJUSTABLE WALL TIE
INSULATION RETAINER

HORIZONTAL REINFORCING WHEN REQUIRED

MORTAR DROP CONTROL

FLASHING MEMBRANE SURFACE ADHERE TO SUBSTRATE

UNOBSTRUCTED WEEP SYSTEM @ 24" O/C

PREFINISHED METAL DRIP EDGE SET ON TWO BEADS OF SEALANT

COMPRESSIBLE BACKER ROD AND SEALANT
PREMOLDED EXPANSION JOINT FILLER

2% SLOPE MIN.

BUILDING PAPER
HIGH SLUMP MASONRY GROUT



ARRISCRAFT
INTERNATIONAL
BUILDING STONE • BRICK • LIMESTONE

ARRISCRAFT • CADD

TITLE:
ALTERNATIVE FOUNDATION WALL/
BURIED MASONRY UNIT

DATE DRAWN:
08/30/04

SCALE:
3"=1'-0"

DRAWN BY:
LPS

DETAIL No:
CB AD04S

U007