



ADAIR® LIMESTONE
MASONRY UNIT,
MIN. 1" AIR SPACE,
RIGID OR SEMI-RIGID
INSULATION (THICKNESS
DEPENDANT ON
REQUIRED R-VALUE),
AIR/VAPOR BARRIER
MEMBRANE,
CONCRETE MASONRY
UNIT (CMU),
METAL FURRING (OPTIONAL),
GYPSUM WALLBOARD.

FLASHING MEMBRANE
SURFACE ADHERE
TO SUBSTRATE
MORTAR DROP
CONTROL
UNOBSTRUCTED
WEEP SYSTEM
@ 24" O/C

CORROSION PROTECTED
STEEL ANGLE LINTEL
COMPRESSIBLE BACKER
ROD AND SEALANT
PREMANUFACTURED
THERMALLY BROKEN
ALUMINUM
WINDOW ASSEMBLY

VERTICAL REINFORCING
IF REQUIRED
HORIZONTAL REINFORCING
WHEN REQUIRED
STEEL REBAR
REINFORCING
CUT CONCRETE BOND
BEAM TO HEIGHT AND
INCLUDE SOAP UNITS AT
END OF BOND BEAM TO
MAINTAIN COURSING OF CMU
WOOD BLOCKING
COMPRESSIBLE
BACKER ROD AND
SEALANT ALL
AROUND THE FRAME
SPRAY APPLIED FOAM
INSULATING AIR SEAL
ALL AROUND FRAME



ARRISCRAFT
INTERNATIONAL
BUILDING STONE • BRICK • LIMESTONE

ARRISCRAFT • CADD

TITLE:
**ALTERNATIVE ALUMINUM
WINDOW HEAD**

DATE DRAWN:
08/30/04

SCALE:
3"=1'-0"

DRAWN BY:
LPS

DETAIL No:
CB AD04S

U032