



ADAIR® LIMESTONE
MASONRY UNIT,
MIN. 1" AIR SPACE,
RIGID OR SEMI-RIGID
INSULATION (THICKNESS
DEPENDANT ON
REQUIRED R-VALUE),
AIR/VAPOR BARRIER
MEMBRANE,
CONCRETE MASONRY
UNIT (CMU),
METAL FURRING (OPTIONAL),
GYPSUM WALLBOARD.

FLASHING MEMBRANE
SURFACE ADHERE
TO SUBSTRATE

MORTAR DROP
CONTROL

UNOBSTRUCTED
WEEP SYSTEM
@ 24" O/C

HORIZONTAL
REINFORCING
WHEN REQUIRED

CUT SOLID CONCRETE
MASONRY TO HEIGHT AND
INCLUDE SOAP UNITS AT
ENDS TO MAINTAIN
COURSING OF CMU

WOOD BLOCKING

COMPRESSION PROTECTED
STEEL ANGLE LINTEL

COMPRESSIBLE BACKER
ROD AND SEALANT

PREMANUFACTURED
THERMALLY BROKEN
ALUMINUM DOOR ASSEMBLY

COMPRESSION PROTECTED
STEEL ANGLE LINTEL

COMPRESSIBLE BACKER
ROD AND SEALANT ALL
AROUND THE FRAME

SPRAY APPLIED FOAM
INSULATING AIR SEAL
ALL AROUND FRAME



ARRISCRAFT
INTERNATIONAL
BUILDING STONE • BRICK • LIMESTONE

ARRISCRAFT • CADD

TITLE:
**ALTERNATIVE ALUMINUM
DOOR HEAD**

DATE DRAWN:
08/30/04

SCALE:
3"=1'-0"

DRAWN BY:
LPS

DETAIL No:
CB AD04S

U063