



MECHANICAL ANCHOR

10
1

RAKE BACK MORTAR
BETWEEN UNITS
APPROX. 1" DEEP
COVER WITH
BACKER ROD AND
SEALANT TO
PROTECT MORTAR

STONE OR
PRECAST CAP

1" MIN.
1-1/2" MIN.
VENT @ 24" O/C

1" MIN.
1-1/2" MIN.
FLEXIBLE FLASHING
MEMBRANE
BELOW STONE OR
PRECAST CAP

ADAIR® LIMESTONE
MASONRY UNIT,
MIN. 1" AIR SPACE,
RIGID OR SEMI-RIGID
INSULATION (THICKNESS
DEPENDANT ON
REQUIRED R-VALUE),
AIR/VAPOR BARRIER
MEMBRANE,
CONCRETE MASONRY
UNIT (CMU).

COVERBOARD

VERTICAL
REINFORCING
IF REQUIRED

ROOF BY OTHER

FLASHING MEMBRANE
SURFACE ADHERE
TO SUBSTRATE

MORTAR DROP
CONTROL

CORROSION PROTECTED
CONTINUOUS STEEL
ANGLE AND
STEEL BRACKET

UNOBSTRUCTED
WEEP SYSTEM @ 24" O/C

3/8" MIN.

COMPRESSIBLE BACKER
ROD AND SEALANT

WELD IN PLACE
STEEL PLATE



ARRISCRAFT
INTERNATIONAL
BUILDING STONE • BRICK • LIMESTONE

ARRISCRAFT • CADD

TITLE:

ALTERNATIVE PARAPET TO WALL
WITH STONE OR PRECAST CAP

DATE DRAWN:
08/30/04

SCALE:
3"=1'-0"

DRAWN BY:
LPS

DETAIL No:

CB AD04S

U123