

ADAIR® LIMESTONE  
 MASONRY UNIT,  
 MIN. 1" AIR SPACE,  
 RIGID OR SEMI-RIGID  
 INSULATION (THICKNESS  
 DEPENDANT ON REQUIRED  
 R-VALUE),  
 AIR/VAPOR BARRIER  
 MEMBRANE,  
 CONCRETE MASONRY UNIT (CMU),  
 METAL FURRING (OPTIONAL),  
 GYPSUM WALLBOARD.

HORIZONTAL  
 REINFORCING  
 WHEN REQUIRED

VERTICAL  
 REINFORCING  
 IF REQUIRED

FLOOR BY OTHER

MORTAR DROP  
 CONTROL

FLASHING MEMBRANE  
 SURFACE ADHERE  
 TO SUBSTRATE

UNOBSTRUCTED  
 WEEP SYSTEM  
 @ 24" O/C

PREFINISHED METAL  
 DRIP EDGE SET ON  
 TWO BEADS OF SEALANT

PARGING

6" MIN.

3/8" MIN.

COMPRESSIBLE BACKER  
 ROD AND SEALANT  
 PREMOLDED EXPANSION  
 JOINT FILLER

2% SLOPE MIN.

BUILDING PAPER

STEEL STUD  
 FURRING WITH  
 INSULATION

GYPSUM  
 WALLBOARD

AIR/VAPOR BARRIER



**ARRISCRAFT**  
 INTERNATIONAL  
 BUILDING STONE • BRICK • LIMESTONE

**ARRISCRAFT • CADD**

TITLE:  
 ALTERNATIVE FOUNDATION TO WALL  
 JUNCTION AND PAVING

DATE DRAWN:  
 08/30/04

SCALE:  
 3"=1'-0"

DRAWN BY:  
 LPS

DETAIL No:  
 CB AD08S

**U003**