



ADJUSTABLE WALL TIE  
INSULATION RETAINER

ADAIR® LIMESTONE MASONRY UNIT, MIN. 1" AIR SPACE, RIGID OR SEMI-RIGID INSULATION (THICKNESS DEPENDANT ON REQUIRED R-VALUE), AIR/VAPOR BARRIER MEMBRANE, CONCRETE MASONRY UNIT (CMU), METAL FURRING (OPTIONAL), GYPSUM WALLBOARD.

MORTAR DROP CONTROL  
FLASHING MEMBRANE SURFACE ADHERE TO SUBSTRATE  
UNOBSTRUCTED WEEP SYSTEM @ 24" O/C  
PREFINISHED METAL DRIP EDGE SET ON TWO BEADS OF SEALANT

HORIZONTAL REINFORCING WHEN REQUIRED  
VERTICAL REINFORCING IF REQUIRED

FLOOR BY OTHER

3/8 MIN.

HIGH SLUMP MASONRY GROUT

BUILDING PAPER  
AIR/VAPOR BARRIER



**ARRISCRAFT**  
INTERNATIONAL  
BUILDING STONE • BRICK • LIMESTONE

**ARRISCRAFT • CADD**

TITLE:  
ALTERNATIVE FOUNDATION WALL/  
BURIED MASONRY UNIT

DATE DRAWN:  
08/30/04

SCALE:  
3"=1'-0"

DRAWN BY:  
LPS

DETAIL No:  
CB AD08S

**U006**