

ADAIR® LIMESTONE
 MASONRY UNIT,
 MIN. 1" AIR SPACE,
 RIGID OR SEMI-RIGID
 INSULATION (THICKNESS
 DEPENDANT ON
 REQUIRED R-VALUE),
 AIR/VAPOR BARRIER
 MEMBRANE,
 CONCRETE MASONRY
 UNIT (CMU),
 METAL FURRING
 (OPTIONAL),
 GYPSUM WALLBOARD.

FLASHING MEMBRANE
 SURFACE AHDERE
 TO SUBSTRATE
 MORTAR DROP
 CONTROL

CORROSION PROTECTED
 CONTINUOUS STEEL ANGLE
 AND STEEL BRACKET

UNOBSTRUCTED
 WEEP SYSTEM
 @ 24" O/C

PREFINISHED METAL
 DRIP EDGE SET ON
 TWO BEADS
 OF SEALANT

VERTICAL
 REINFORCING
 IF REQUIRED

FLOOR BY
 OTHER

3/8" MIN.

PAVING

6" MIN.

COMPRESSIBLE BACKER
 ROD AND SEALANT

PREMOLDED EXPANSION
 JOINT FILLER

2% SLOPE MIN.

WELD PLATE
 CAST IN PLACE
 BUILDING
 PAPER
 STEEL STUD
 FURRING WITH
 INSULATION
 AIR/VAPOR
 BARRIER



ARRISCRAFT
 INTERNATIONAL
 BUILDING STONE • BRICK • LIMESTONE

ARRISCRAFT • CADD

TITLE:
 ALTERNATIVE FOUNDATION TO WALL
 (SHELF ANGLE) AND PAVING

DATE DRAWN:
 08/30/04

SCALE:
 3"=1'-0"

DRAWN BY:
 LPS

DETAIL No:
 CB AD08S
U009