



WOOD BLOCKING
 BACKER ROD AND SEALANT
 BULLNOSE SILL
 CALCIUM SILICATE MASONRY UNIT (CSMU)
 MASONRY TIE OR MECHANICAL ANCHOR IN HEAD JOINT
 RAKE BACK MORTAR BETWEEN UNITS APPROX. 1" DEEP. COVER WITH BACKER ROD AND SEALANT TO PROTECT MORTAR

PREMANUFACTURED THERMALLY BROKEN ALUMINUM WINDOW ASSEMBLY
 SPRAY APPLIED FOAM INSULATING AIR SEAL ALL AROUND FRAME
 BACKER ROD AND SEALANT ALL AROUND THE FRAME
 WOOD BLOCKING

UNDERSILL FLASHING MEMBRANE C/W END DAMS, INSTALL TUBE VENTS AT CENTER OF BULLNOSE UNITS
 VENT @ 24" O/C

SOLID CONCRETE MASONRY UNIT
 HORIZONTAL REINFORCING WHEN REQUIRED
 ASHLAR BLOCK
 ADAIR® LIMESTONE MASONRY UNIT, MIN. 1" AIR SPACE, RIGID OR SEMI-RIGID INSULATION (THICKNESS DEPENDANT ON REQUIRED R-VALUE), AIR/VAPOR BARRIER MEMBRANE, CONCRETE MASONRY UNIT (CMU), METAL FURRING (OPTIONAL), GYPSUM WALLBOARD.

INSULATION RETAINER
 ADJUSTABLE WALL TIE



ARRISCRAFT
 INTERNATIONAL
 BUILDING STONE • BRICK • LIMESTONE

ARRISCRAFT • CADD

TITLE:
BULLNOSE WINDOW SILL

DATE DRAWN:
 08/30/04

SCALE:
 3"=1'-0"

DRAWN BY:
 LPS

DETAIL No:
 CB AD08S

U021