

ADAIR® LIMESTONE  
MASONRY UNIT,  
MIN. 1" AIR SPACE,  
RIGID OR SEMI-RIGID  
INSULATION (THICKNESS  
DEPENDANT ON REQUIRED  
R-VALUE),  
AIR/VAPOR BARRIER  
MEMBRANE,  
CONCRETE  
MASONRY UNIT (CMU),  
METAL FURRING (OPTIONAL),  
GYPSUM WALLBOARD.

COMPRESSIBLE BACKER  
ROD AND SEALANT

SEALANT BEADS FOR  
MOISTURE PROTECTION

SLOPE AWAY TO ENSURE  
WATER DRAINAGE

FLASHING MEMBRANE  
SURFACE ADHERE  
TO SUBSTRATE

PREMANUFACTURED  
THERMALLY BROKEN  
ALUMINUM DOOR  
ASSEMBLY

FLOOR BY OTHER

PARGING

COMPRESSIBLE BACKER  
ROD AND SEALANT  
PREMOLDED EXPANSION  
JOINT FILLER

2% SLOPE MIN.

BUILDING PAPER

AIR/VAPOR BARRIER

STEEL STUD  
FURRING WITH  
INSULATION



**ARRISCRAFT**  
INTERNATIONAL  
BUILDING STONE • BRICK • LIMESTONE

**ARRISCRAFT • CADD**

TITLE:

THRESHOLD OF DOOR

DATE DRAWN:  
08/30/04

SCALE:  
3"=1'-0"

DRAWN BY:  
LPS

DETAIL No:  
CB AD08S

**U050**