

ADAIR® LIMESTONE  
MASONRY UNIT,  
MIN. 1" AIR SPACE,  
RIGID OR SEMI-RIGID  
INSULATION (THICKNESS  
DEPENDANT ON REQUIRED  
R-VALUE),  
AIR/VAPOR BARRIER  
MEMBRANE,  
CONCRETE  
MASONRY UNIT (CMU),  
METAL FURRING (OPTIONAL),  
GYPSUM WALLBOARD.

PREMANUFACTURED  
THERMALLY BROKEN  
DOOR ASSEMBLY

FLOOR BY OTHER

SEALANT BEADS FOR  
MOISTURE PROTECTION  
SLOPE AWAY TO ENSURE  
WATER DRAINAGE

FLASHING MEMBRANE  
SURFACE ADHERE  
TO SUBSTRATE

HIGH SLUMP MASONRY GROUT  
COMPRESSIBLE BACKER  
ROD AND SEALANT  
PREMOLDED EXPANSION  
JOINT FILLER

2% SLOPE MIN.

BUILDING PAPER

AIR/VAPOR BARRIER

STEEL STUD  
FURRING WITH  
INSULATION



**ARRISCRAFT**  
INTERNATIONAL  
BUILDING STONE • BRICK • LIMESTONE

**ARRISCRAFT • CADD**

TITLE:

ALTERNATIVE  
THRESHOLD OF DOOR

DATE DRAWN:  
08/30/04

SCALE:  
3"=1'-0"

DRAWN BY:  
LPS

DETAIL No:

CB AD08S

**U051**