



ADAIR® LIMESTONE
 MASONRY UNIT,
 MIN. 1" AIR SPACE,
 RIGID OR SEMI-RIGID
 INSULATION (THICKNESS
 DEPENDANT ON REQUIRED
 R-VALUE),
 AIR/VAPOR BARRIER
 MEMBRANE,
 CONCRETE
 MASONRY UNIT (CMU),
 METAL FURRING (OPTIONAL),
 GYPSUM WALLBOARD.

FLASHING MEMBRANE
 SURFACE ADHERE
 TO SUBSTRATE

MORTAR DROP
 CONTROL

UNOBSTRUCTED
 WEEP SYSTEM
 @ 24" O/C

PREFINISHED
 METAL DRIP EDGE
 SET ON TWO
 BEADS OF SEALANT

CORROSION PROTECTED
 STEEL ANGLE LINTEL

COMPRESSIBLE BACKER
 ROD AND SEALANT

PREMANUFACTURED
 THERMALLY BROKEN
 ALUMINUM DOOR ASSEMBLY

VERTICAL REINFORCING
 IF REQUIRED

HORIZONTAL REINFORCING
 WHEN REQUIRED

STEEL REBAR
 REINFORCING

CUT CONCRETE BOND
 BEAM TO HEIGHT AND
 INCLUDE SOAP UNITS AT
 END OF BOND BEAM TO
 MAINTAIN COURSING OF CMU

WOOD BLOCKING

COMPRESSIBLE
 BACKER ROD AND
 SEALANT ALL
 AROUND THE FRAME

SPRAY APPLIED FOAM
 INSULATING AIR SEAL
 ALL AROUND FRAME



ARRISCRAFT
 INTERNATIONAL
 BUILDING STONE • BRICK • LIMESTONE

ARRISCRAFT • CADD

TITLE:
**ALUMINUM DOOR
 HEAD**

DATE DRAWN:
 08/30/04

SCALE:
 3"=1'-0"

DRAWN BY:
 LPS

DETAIL No:
 CB AD08S

U060