



ADAIR® LIMESTONE
 MASONRY UNIT,
 MIN. 1" AIR SPACE,
 RIGID OR SEMI-RIGID
 INSULATION (THICKNESS
 DEPENDANT ON REQUIRED
 R-VALUE),
 AIR/VAPOR BARRIER
 MEMBRANE,
 CONCRETE
 MASONRY UNIT (CMU),
 METAL FURRING (OPTIONAL),
 GYPSUM WALLBOARD.

FLASHING MEMBRANE
 SURFACE ADHERE
 TO SUBSTRATE
 MORTAR DROP
 CONTROL
 UNOBSTRUCTED
 WEEP SYSTEM
 @ 24" O/C

CORROSION PROTECTED
 STEEL ANGLE LINTEL
 COMPRESSIBLE BACKER
 ROD AND SEALANT

PREMANUFACTURED
 THERMALLY BROKEN
 ALUMINUM DOOR ASSEMBLY

VERTICAL REINFORCING
 IF REQUIRED
 HORIZONTAL REINFORCING
 WHEN REQUIRED
 STEEL REBAR
 REINFORCING
 CUT CONCRETE BOND
 BEAM TO HEIGHT AND
 INCLUDE SOAP UNITS AT
 END OF BOND BEAM TO
 MAINTAIN COURSING OF CMU
 WOOD BLOCKING

COMPRESSIBLE
 BACKER ROD AND
 SEALANT ALL
 AROUND THE FRAME

SPRAY APPLIED FOAM
 INSULATING AIR SEAL
 ALL AROUND FRAME



ARRISCRAFT
 INTERNATIONAL
 BUILDING STONE • BRICK • LIMESTONE

ARRISCRAFT • CADD

TITLE:
**ALTERNATIVE ALUMINUM
 DOOR HEAD**

DATE DRAWN:
 08/30/04

SCALE:
 3"=1'-0"

DRAWN BY:
 LPS

DETAIL No:
 CB AD08S

U062