



MECHANICAL ANCHOR

10  
1

RAKE BACK MORTAR  
BETWEEN UNITS  
APPROX. 1" DEEP  
COVER WITH  
BACKER ROD AND  
SEALANT TO  
PROTECT MORTAR

STONE OR  
PRECAST CAP

1" MIN.  
1-1/2" MIN.  
VENT @ 24" O/C

1" MIN.  
1-1/2" MIN.  
FLEXIBLE FLASHING  
MEMBRANE  
BELOW STONE OR  
PRECAST CAP

ADAIR® LIMESTONE  
MASONRY UNIT,  
MIN. 1" AIR SPACE,  
RIGID OR SEMI-RIGID  
INSULATION (THICKNESS  
DEPENDANT ON  
REQUIRED R-VALUE),  
AIR/VAPOR BARRIER  
MEMBRANE,  
CONCRETE MASONRY  
UNIT (CMU).

COVERBOARD

VERTICAL  
REINFORCING  
IF REQUIRED

ROOF BY OTHER

FLASHING MEMBRANE  
SURFACE ADHERE  
TO SUBSTRATE

MORTAR DROP  
CONTROL

CORROSION PROTECTED  
CONTINUOUS STEEL  
ANGLE AND  
STEEL BRACKET

UNOBSTRUCTED  
WEEP SYSTEM @ 24" O/C

WELD IN PLACE  
STEEL PLATE

3/8" MIN.

COMPRESSIBLE BACKER  
ROD AND SEALANT



**ARRISCRAFT**  
INTERNATIONAL  
BUILDING STONE • BRICK • LIMESTONE

**ARRISCRAFT • CADD**

TITLE:

ALTERNATIVE PARAPET TO WALL  
WITH STONE OR PRECAST CAP

DATE DRAWN:  
08/30/04

SCALE:  
3"=1'-0"

DRAWN BY:  
LPS

DETAIL No:

CB AD08S

**U123**