

ADAIR® LIMESTONE  
MASONRY UNIT,  
MIN. 25 MM AIR SPACE,  
RIGID OR SEMI-RIGID INSULATION  
(THICKNESS DEPENDANT ON  
REQUIRED R-VALUE),  
AIR/VAPOUR BARRIER  
MEMBRANE,  
CONCRETE MASONRY UNIT (CMU),  
METAL FURRING (OPTIONAL),  
GYPSUM WALLBOARD.

HORIZONTAL  
REINFORCING  
WHEN REQUIRED

VERTICAL  
REINFORCING  
IF REQUIRED

FLOOR BY  
OTHER

MORTAR DROP  
CONTROL

FLASHING MEMBRANE  
SURFACE ADHERE  
TO SUBSTRATE

UNOBSTRUCTED  
WEEP SYSTEM  
@ 600 MM O/C

PREFINISHED METAL  
DRIP EDGE SET ON  
TWO BEADS OF SEALANT

10 MIN.  
CORROSION PROTECTED  
CONTINUOUS STEEL ANGLE  
AND STEEL BRACKET  
PARGING

WELD PLATE  
CAST IN PLACE  
AIR/VAPOUR  
BARRIER  
BUILDING PAPER  
STEEL STUD  
FURRING WITH  
INSULATION



**ARRISCRAFT**  
INTERNATIONAL  
BUILDING STONE • BRICK • LIMESTONE

**ARRISCRAFT • CADD**

TITLE:  
ALTERNATIVE FOUNDATION TO WALL  
(SHELF ANGLE)

DATE DRAWN:  
08/30/04

SCALE:  
1:5

DRAWN BY:  
LPS

DETAIL No:  
CB AD09S

**D008**