

ADAIR® LIMESTONE  
 MASONRY UNIT,  
 MIN. 25 MM AIR SPACE,  
 RIGID OR SEMI-RIGID INSULATION  
 (THICKNESS DEPENDANT ON  
 REQUIRED R-VALUE),  
 AIR/VAPOUR BARRIER  
 MEMBRANE,  
 CONCRETE MASONRY UNIT (CMU),  
 METAL FURRING (OPTIONAL),  
 GYPSUM WALLBOARD.

PREMANUFACTURED  
 THERMALLY BROKEN  
 DOOR ASSEMBLY

SEALANT BEADS FOR  
 MOISTURE PROTECTION

SLOPE AWAY TO ENSURE  
 WATER DRAINAGE

FLASHING MEMBRANE  
 SURFACE ADHERE  
 TO SUBSTRATE

FLOOR BY OTHER

150 MIN.  
 2% SLOPE MIN.

ADAIR® LIMESTONE  
 MARBLE BASE COURSE  
 COMPRESSIBLE BACKER  
 ROD AND SEALANT  
 PREMOULDED EXPANSION  
 JOINT FILLER

AIR/VAPOUR BARRIER  
 BUILDING PAPER



**ARRISCRAFT**  
 INTERNATIONAL  
 BUILDING STONE • BRICK • LIMESTONE

**ARRISCRAFT • CADD**

TITLE:  
 ALTERNATIVE  
 THRESHOLD OF DOOR

DATE DRAWN:  
 08/30/04

SCALE:  
 1:5

DRAWN BY:  
 LPS

DETAIL No:  
 CB AD09S

**D051**