



GYPSUM WALLBOARD,
 METAL FURRING (OPTIONAL),
 CONCRETE MASONRY UNIT (CMU),
 AIR/VAPOUR BARRIER
 MEMBRANE,
 RIGID OR SEMI-RIGID INSULATION
 (THICKNESS DEPENDANT
 ON REQUIRED R-VALUE),
 MIN. 25 MM AIR SPACE,
 ADAIR® LIMESTONE MASONRY UNIT.

HORIZONTAL
 REINFORCING
 WHEN REQUIRED

RAKE BACK MORTAR BETWEEN
 UNITS APPROX. 25 MM DEEP. COVER
 WITH BACKER ROD AND SEALANT
 TO PROTECT MORTAR

INSULATION RETAINER
 ADJUSTABLE WALL TIE
 HORIZONTAL REINFORCING
 IN BED JOINTS TO REINFORCE
 CONTINUOUS VERTICAL
 CORNER JOINTS



ARRISCRAFT
 INTERNATIONAL
 BUILDING STONE • BRICK • LIMESTONE

ARRISCRAFT • CADD

TITLE:
 QUIRK MITRED OUTSIDE
 CORNER

DATE DRAWN:
 08/30/04

SCALE:
 1:5

DRAWN BY:
 LPS

DETAIL No:
 CB AD09S

D150