



ADJUSTABLE  
WALL TIE

INSULATION  
RETAINER

ADAIR® LIMESTONE  
MASONRY UNIT,  
MIN. 1" AIR SPACE,  
RIGID OR SEMI-RIGID  
INSULATION (THICKNESS  
DEPENDANT ON  
REQUIRED R-VALUE),  
AIR/VAPOR BARRIER  
MEMBRANE,  
CONCRETE MASONRY  
UNIT (CMU),  
METAL FURRING (OPTIONAL),  
GYPSUM WALLBOARD.

MORTAR DROP  
CONTROL

FLASHING MEMBRANE  
SURFACE ADHERE  
TO SUBSTRATE

UNOBSTRUCTED  
WEEP SYSTEM  
@ 24" O/C

PREFINISHED METAL  
DRIP EDGE SET ON  
TWO BEADS OF SEALANT

HORIZONTAL  
REINFORCING  
WHEN REQUIRED

VERTICAL  
REINFORCING  
IF REQUIRED

3/8 MIN.

FLOOR BY OTHER

HIGH SLUMP  
MASONRY GROUT

BUILDING PAPER

AIR/VAPOR BARRIER



**ARRISCRAFT**  
INTERNATIONAL  
BUILDING STONE • BRICK • LIMESTONE

**ARRISCRAFT • CADD**

TITLE:  
ALTERNATIVE FOUNDATION WALL/  
BURIED MASONRY UNIT

DATE DRAWN:  
08/30/04

SCALE:  
3"=1'-0"

DRAWN BY:  
LPS

DETAIL No:  
CB AD12S

**U006**