

ADAIR® LIMESTONE
MASONRY UNIT,
MIN. 1" AIR SPACE,
RIGID OR SEMI-RIGID
INSULATION (THICKNESS
DEPENDANT ON REQUIRED
R-VALUE),
AIR/VAPOR BARRIER
MEMBRANE,
CONCRETE MASONRY UNIT (CMU),
METAL FURRING (OPTIONAL),
GYPSUM WALLBOARD.

COMPRESSIBLE BACKER
ROD AND SEALANT

SEALANT BEADS FOR
MOISTURE PROTECTION

SLOPE AWAY TO ENSURE
WATER DRAINAGE

FLASHING MEMBRANE
SURFACE ADHERE
TO SUBSTRATE

PREMANUFACTURED
THERMALLY BROKEN
ALUMINUM DOOR
ASSEMBLY

FLOOR BY OTHER

PARGING

COMPRESSIBLE BACKER
ROD AND SEALANT

PREMOLDED EXPANSION
JOINT FILLER

2% SLOPE MIN.

BUILDING PAPER

AIR/VAPOR BARRIER

STEEL STUD
FURRING WITH
INSULATION



ARRISCRAFT
INTERNATIONAL
BUILDING STONE • BRICK • LIMESTONE

ARRISCRAFT • CADD

TITLE:

THRESHOLD OF DOOR

DATE DRAWN:

08/30/04

SCALE:

3"=1'-0"

DRAWN BY:

LPS

DETAIL No:

CB AD12S

U050