

ADAIR® LIMESTONE
 MASONRY UNIT,
 MIN. 1" AIR SPACE,
 RIGID OR SEMI-RIGID
 INSULATION (THICKNESS
 DEPENDANT ON REQUIRED
 R-VALUE),
 AIR/VAPOR BARRIER
 MEMBRANE,
 CONCRETE MASONRY UNIT (CMU),
 METAL FURRING (OPTIONAL),
 GYPSUM WALLBOARD.

PREMANUFACTURED
 THERMALLY BROKEN
 DOOR ASSEMBLY

SEALANT BEADS FOR
 MOISTURE PROTECTION
 SLOPE AWAY TO ENSURE
 WATER DRAINAGE

FLASHING MEMBRANE
 SURFACE ADHERE
 TO SUBSTRATE

FLOOR BY OTHER

HIGH SLUMP MASONRY GROUT
 COMPRESSIBLE BACKER
 ROD AND SEALANT
 PREMOLDED EXPANSION
 JOINT FILLER

2% SLOPE MIN.

BUILDING PAPER
 AIR/VAPOR BARRIER
 STEEL STUD
 FURRING WITH
 INSULATION



ARRISCRAFT
 INTERNATIONAL
 BUILDING STONE • BRICK • LIMESTONE

ARRISCRAFT • CADD

TITLE:

ALTERNATIVE
 THRESHOLD OF DOOR

DATE DRAWN:

08/30/04

SCALE:

3"=1'-0"

DRAWN BY:

LPS

DETAIL No:

CB AD12S

U051