



SUBSTRATE

EIFS WITH
DRAINAGE BOARD/
STUCCO

PREFINISHED METAL
DRIP FLASHING

BACKER ROD
AND SEALANT

BULLNOSE WATERTABLE
CALCIUM SILICATE
MASONRY UNIT (CSMU)

MASONRY TIE OR
MECHANICAL ANCHOR
IN HEAD JOINT

HORIZONTAL
REINFORCING
WHEN REQUIRED

RAKE BACK MORTAR
BETWEEN UNITS APPROX.
1" DEEP. COVER WITH
BACKER ROD AND SEALANT
TO PROTECT MORTAR

1" MIN.

VENT @ 24" O/C

INSULATION
RETAINER

ADJUSTABLE
WALL TIE

GYPSUM WALLBOARD,
METAL FURRING
(OPTIONAL),
CONCRETE MASONRY
UNIT (CMU),
AIR/VAPOR BARRIER
MEMBRANE,
RIGID OR SEMI-RIGID
INSULATION (THICKNESS
DEPENDANT ON
REQUIRED R-VALUE),
MIN. 1" AIR SPACE,
ADAIR® LIMESTONE
MASONRY UNIT.



ARRISCRAFT
INTERNATIONAL
BUILDING STONE • BRICK • LIMESTONE

ARRISCRAFT • CADD

TITLE:
EIFS/CALCIUM SILICATE
TRANSITION (BULLNOSE)

DATE DRAWN:
08/30/04

SCALE:
3"=1'-0"

DRAWN BY:
LPS

DETAIL No:
CB AD12S

U103