



MECHANICAL ANCHOR

10
1

RAKE BACK MORTAR BETWEEN UNITS APPROX. 1" DEEP COVER WITH BACKER ROD AND SEALANT TO PROTECT MORTAR

STONE OR PRECAST CAP

1" MIN.
1-1/2" MIN.

VENT @ 24" O/C

FLEXIBLE FLASHING MEMBRANE BELOW STONE OR PRECAST CAP

COVERBOARD

VERTICAL REINFORCING IF REQUIRED

ROOF BY OTHER

ADAIR® LIMESTONE MASONRY UNIT, MIN. 1" AIR SPACE, RIGID OR SEMI-RIGID INSULATION (THICKNESS DEPENDANT ON REQUIRED R-VALUE), AIR/VAPOR BARRIER MEMBRANE, CONCRETE MASONRY UNIT (CMU).

FLASHING MEMBRANE SURFACE ADHERE TO SUBSTRATE

MORTAR DROP CONTROL

CORROSION PROTECTED CONTINUOUS STEEL ANGLE AND STEEL BRACKET

UNOBSTRUCTED WEEP SYSTEM @ 24" O/C

3/8" MIN.

COMPRESSIBLE BACKER ROD AND SEALANT

WELD IN PLACE STEEL PLATE



ARRISCRAFT
INTERNATIONAL
BUILDING STONE • BRICK • LIMESTONE

ARRISCRAFT • CADD

TITLE:
ALTERNATIVE PARAPET TO WALL
WITH STONE OR PRECAST CAP

DATE DRAWN:
08/30/04

SCALE:
3/8"=1'-0"

DRAWN BY:
LPS

DETAIL No:
CB AD12S

U123