



CALCIUM SILICATE BUILDING STONE, MIN. 1" AIR SPACE, RIGID OR SEMI-RIGID INSULATION (THICKNESS DEPENDANT ON REQUIRED R-VALUE), AIR/VAPOR BARRIER MEMBRANE, CONCRETE MASONRY UNIT (CMU), METAL FURRING (OPTIONAL), GYPSUM WALLBOARD.

MORTAR DROP CONTROL  
FLASHING MEMBRANE SURFACE ADHERE TO SUBSTRATE UNOBSTRUCTED WEEP SYSTEM @ 24" O/C  
PREFINISHED METAL DRIP EDGE SET ON TWO BEADS OF SEALANT

HIGH SLUMP MASONRY GROUT  
DRAINAGE TILE

HORIZONTAL REINFORCING WHEN REQUIRED

VERTICAL REINFORCING IF REQUIRED

FLOOR BY OTHER

AIR/VAPOR BARRIER

BUILDING PAPER

STEEL STUD FURRING WITH INSULATION

GRAVEL MOWING STRIP

**ARRISCRAFT • CADD**

DATE DRAWN:  
08/30/04

DETAIL No:  
CB CD3I

TITLE:  
FOUNDATION WALL/  
BURIED MASONRY UNIT  
(GRAVEL MOWING STRIP AND FRENCH DRAIN)

SCALE:  
3"=1'-0"

DRAWN BY:  
LPS

**U004**

