



CALCIUM SILICATE BUILDING STONE, MIN. 1" AIR SPACE, RIGID OR SEMI-RIGID INSULATION (THICKNESS DEPENDANT ON REQUIRED R-VALUE), AIR/VAPOR BARRIER MEMBRANE, CONCRETE MASONRY UNIT (CMU), METAL FURRING (OPTIONAL), GYPSUM WALLBOARD.

FLASHING MEMBRANE SURFACE ADHERE TO SUBSTRATE

MORTAR DROP CONTROL

UNOBSTRUCTED WEEP SYSTEM @ 24" O/C

PREFINISHED METAL DRIP EDGE SET ON TWO BEADS OF SEALANT

3/8 MIN.

CORROSION PROTECTED CONTINUOUS STEEL ANGLE AND STEEL BRACKET

6" MIN.

PARGING

HORIZONTAL REINFORCING WHEN REQUIRED

VERTICAL REINFORCING IF REQUIRED

FLOOR BY OTHER

WELD PLATE CAST IN PLACE

BUILDING PAPER

STEEL STUD FURRING WITH INSULATION

AIR/VAPOR BARRIER



ARRISCRAFT
INTERNATIONAL
BUILDING STONE • BRICK • LIMESTONE

ARRISCRAFT • CADD

TITLE:
ALTERNATIVE FOUNDATION TO WALL
(SHELF ANGLE) WITH SOIL

DATE DRAWN:
08/30/04

SCALE:
3"=1'-0"

DRAWN BY:
LPS

DETAIL No:
CB CD3I

U007