



CALCIUM SILICATE BUILDING STONE, MIN. 1" AIR SPACE, RIGID OR SEMI-RIGID INSULATION (THICKNESS DEPENDANT ON REQUIRED R-VALUE), AIR/VAPOR BARRIER MEMBRANE, CONCRETE MASONRY UNIT (CMU), METAL FURRING (OPTIONAL), GYPSUM WALLBOARD.

FLASHING MEMBRANE SURFACE ADHERE TO SUBSTRATE

MORTAR DROP CONTROL

UNOBSTRUCTED WEEP SYSTEM @ 24" O/C

CORROSION PROTECTED STEEL ANGLE LINTEL

COMPRESSIBLE BACKER ROD AND SEALANT

PREMANUFACTURED THERMALLY BROKEN ALUMINUM WINDOW ASSEMBLY

HORIZONTAL REINFORCING WHEN REQUIRED

CUT SOLID CONCRETE MASONRY TO HEIGHT AND INCLUDE SOAP UNITS AT ENDS TO MAINTAIN COURSING OF CMU

WOOD BLOCKING

COMPRESSIBLE BACKER ROD AND SEALANT ALL AROUND THE FRAME

SPRAY APPLIED FOAM INSULATING AIR SEAL ALL AROUND FRAME



**ARRISCRAFT**  
INTERNATIONAL  
BUILDING STONE • BRICK • LIMESTONE

**ARRISCRAFT • CADD**

TITLE:  
**ALTERNATIVE ALUMINUM WINDOW HEAD**

DATE DRAWN:  
08/30/04

SCALE:  
3"=1'-0"

DRAWN BY:  
LPS

DETAIL No:  
CB CD3I

**U033**