



CALCIUM SILICATE
BUILDING STONE,
MIN. 1" AIR SPACE,
RIGID OR SEMI-RIGID
INSULATION (THICKNESS
DEPENDANT ON
REQUIRED R-VALUE),
AIR/VAPOR BARRIER
MEMBRANE,
CONCRETE MASONRY
UNIT (CMU),
METAL FURRING
(OPTIONAL),
GYPSUM WALLBOARD.

PREMANUFACTURED
THERMALLY BROKEN
ALUMINUM DOOR
ASSEMBLY

COMPRESSIBLE BACKER
ROD AND SEALANT

SEALANT BEADS FOR
MOISTURE PROTECTION

SLOPE AWAY TO ENSURE
WATER DRAINAGE

FLASHING MEMBRANE
SURFACE ADHERE
TO SUBSTRATE

FLOOR BY OTHER

PARGING

COMPRESSIBLE BACKER
ROD AND SEALANT

PREMOLDED EXPANSION
JOINT FILLER

2% SLOPE MIN.

BUILDING PAPER

AIR/VAPOR BARRIER



ARRISCRAFT
INTERNATIONAL
BUILDING STONE • BRICK • LIMESTONE

ARRISCRAFT • CADD

TITLE:
THRESHOLD OF DOOR

DATE DRAWN:
08/30/04

SCALE:
3"=1'-0"

DRAWN BY:
LPS

DETAIL No:
CB CD3I

U050