



MECHANICAL ANCHOR

10
1

RAKE BACK MORTAR BETWEEN UNITS APPROX. 1" DEEP COVER WITH BACKER ROD AND SEALANT TO PROTECT MORTAR

STONE OR PRECAST CAP

1" MIN.
1-1/2" MIN.

1" MIN.
1-1/2" MIN.

FLEXIBLE FLASHING MEMBRANE BELOW STONE OR PRECAST CAP

VENT @ 24" O/C
CALCIUM SILICATE BUILDING STONE, MIN. 1" AIR SPACE, RIGID OR SEMI-RIGID INSULATION (THICKNESS DEPENDANT ON REQUIRED R-VALUE), AIR/VAPOR BARRIER MEMBRANE, CONCRETE MASONRY UNIT (CMU).

COVERBOARD

ROOF BY OTHER

VERTICAL REINFORCING IF REQUIRED

FLASHING MEMBRANE SURFACE ADHERE TO SUBSTRATE

MORTAR DROP CONTROL

CORROSION PROTECTED CONTINUOUS STEEL ANGLE AND STEEL BRACKET

UNOBSTRUCTED WEEP SYSTEM @ 24" O/C

3/8" MIN.

COMPRESSIBLE BACKER ROD AND SEALANT

WELD IN PLACE STEEL PLATE



ARRISCRAFT
INTERNATIONAL
BUILDING STONE • BRICK • LIMESTONE

ARRISCRAFT • CADD

TITLE:
ALTERNATIVE PARAPET TO WALL WITH STONE OR PRECAST CAP

DATE DRAWN:
08/30/04

SCALE:
3"=1'-0"

DRAWN BY:
LPS

DETAIL No:
CB CD3I

U123