

ADAIR® LIMESTONE  
MASONRY UNIT,  
MIN. 1" AIR SPACE,  
RIGID OR SEMI-RIGID  
INSULATION (THICKNESS  
DEPENDANT ON REQUIRED  
R-VALUE),  
AIR/VAPOR BARRIER  
MEMBRANE,  
CONCRETE MASONRY UNIT (CMU),  
METAL FURRING (OPTIONAL),  
GYPSUM WALLBOARD.

HORIZONTAL  
REINFORCING  
WHEN REQUIRED

VERTICAL  
REINFORCING  
IF REQUIRED

FLOOR BY OTHER

MORTAR DROP  
CONTROL

FLASHING MEMBRANE  
SURFACE ADHERE  
TO SUBSTRATE

UNOBSTRUCTED  
WEEP SYSTEM  
@ 24" O/C

PREFINISHED METAL  
DRIP EDGE SET ON  
TWO BEADS OF SEALANT

PARGING

6" MIN.

3/8" MIN.

COMPRESSIBLE BACKER  
ROD AND SEALANT  
PREMOLDED EXPANSION  
JOINT FILLER


2% SLOPE MIN.

BUILDING PAPER

STEEL STUD  
FURRING WITH  
INSULATION

GYPSUM  
WALLBOARD

AIR/VAPOR BARRIER



**ARRISCRAFT • CADD**

TITLE:  
ALTERNATIVE FOUNDATION TO WALL  
JUNCTION AND PAVING

DATE DRAWN:  
08/30/04

SCALE:  
3"=1'-0"

DRAWN BY:  
LPS

DETAIL No:  
CBI AD12S

**U003**