

ADAIR® LIMESTONE  
 MASONRY UNIT,  
 MIN. 1" AIR SPACE,  
 RIGID OR SEMI-RIGID  
 INSULATION (THICKNESS  
 DEPENDANT ON REQUIRED  
 R-VALUE),  
 AIR/VAPOR BARRIER  
 MEMBRANE,  
 CONCRETE MASONRY UNIT (CMU),  
 METAL FURRING (OPTIONAL),  
 GYPSUM WALLBOARD.

COMPRESSIBLE BACKER  
 ROD AND SEALANT

SEALANT BEADS FOR  
 MOISTURE PROTECTION

SLOPE AWAY TO ENSURE  
 WATER DRAINAGE

FLASHING MEMBRANE  
 SURFACE ADHERE  
 TO SUBSTRATE

PREMANUFACTURED  
 THERMALLY BROKEN  
 ALUMINUM DOOR  
 ASSEMBLY

FLOOR BY OTHER

PARGING

COMPRESSIBLE BACKER  
 ROD AND SEALANT

PREMOLDED EXPANSION  
 JOINT FILLER

2% SLOPE MIN.

BUILDING PAPER

AIR/VAPOR BARRIER

STEEL STUD  
 FURRING WITH  
 INSULATION



**ARRISCRAFT**  
 INTERNATIONAL  
 BUILDING STONE • BRICK • LIMESTONE

**ARRISCRAFT • CADD**

TITLE:

THRESHOLD OF DOOR

DATE DRAWN:  
 08/30/04

SCALE:  
 3"=1'-0"

DRAWN BY:  
 LPS

DETAIL No:  
 CBI AD12S

**U050**