



INSULATION
RETAINER

ADJUSTABLE WALL TIE

ADAIR® LIMESTONE
MASONRY UNIT,
MIN. 1" AIR SPACE,
RIGID OR SEMI-RIGID
INSULATION (THICKNESS
DEPENDANT ON REQUIRED
R-VALUE),
AIR/VAPOR BARRIER
MEMBRANE,
CONCRETE
MASONRY UNIT (CMU),
METAL FURRING
(OPTIONAL),
GYPSUM WALLBOARD.

HORIZONTAL
REINFORCING
WHEN REQUIRED

INCREASE
REINFORCEMENT
FREQUENCY
AROUND OPENINGS

VERTICAL
REINFORCING
IF REQUIRED

WOOD BLOCKING

COMPRESSIBLE BACKER
ROD AND SEALANT

COMPRESSIBLE
BACKER ROD
AND SEALANT ALL
AROUND THE FRAME

PREMANUFACTURED
THERMALLY BROKEN
ALUMINUM
DOOR ASSEMBLY

SPRAY APPLIED FOAM
INSULATING AIR SEAL
ALL AROUND FRAME



ARRISCRAFT
INTERNATIONAL
BUILDING STONE • BRICK • LIMESTONE

ARRISCRAFT • CADD

TITLE:
**ALUMINUM DOOR
JAMB (PLAN VIEW)**

DATE DRAWN:
08/30/04

SCALE:
3"=1'-0"

DRAWN BY:
LPS

DETAIL No:
**CBI AD12S
U070**