



MORTAR DROP CONTROL

FLASHING MEMBRANE SURFACE ADHERE TO SUBSTRATE

UNOBSTRUCTED WEEP SYSTEM @ 24" O/C

PREFINISHED METAL DRIP EDGE SET ON TWO BEADS OF SEALANT

ADAIR® LIMESTONE MARBLE BASE COURSE

HIGH SLUMP MASONRY GROUT

BALCONY SUPPORTED BY POSTS AT EXTERIOR EDGES

2% SLOPE MIN.

COMPRESSIBLE BACKER ROD AND SEALANT

VENT @ 24" O/C

CORROSION PROTECTED CONTINUOUS STEEL ANGLE AND STEEL BRACKET

HORIZONTAL REINFORCING WHEN REQUIRED

ADAIR® LIMESTONE MASONRY UNIT, MIN. 1" AIR SPACE, RIGID OR SEMI-RIGID INSULATION (THICKNESS DEPENDANT ON REQUIRED R-VALUE), AIR/VAPOR BARRIER MEMBRANE, CONCRETE MASONRY UNIT (CMU), METAL FURRING (OPTIONAL), GYPSUM WALLBOARD.

VERTICAL REINFORCING IF REQUIRED

FLOOR BY OTHER

WELD PLATE CAST IN PLACE

LOADBEARING CORROSION PROTECTED STEEL CHANNEL



**ARRISCRAFT • CADD**

TITLE: BALCONY/WALL WITH ADAIR® BASE COURSE

DATE DRAWN: 08/30/04

SCALE: 3"=1'-0"

DRAWN BY: LPS

DETAIL No: CBI AD12S U091