



SUBSTRATE

EIFS WITH  
DRAINAGE BOARD/  
STUCCO

PREFINISHED METAL  
DRIP FLASHING

BACKER ROD  
AND SEALANT

BULLNOSE WATERTABLE  
CALCIUM SILICATE  
MASONRY UNIT (CSMU)

MASONRY TIE OR  
MECHANICAL ANCHOR  
IN HEAD JOINT

HORIZONTAL  
REINFORCING  
WHEN REQUIRED

RAKE BACK MORTAR  
BETWEEN UNITS APPROX.  
1" DEEP. COVER WITH  
BACKER ROD AND SEALANT  
TO PROTECT MORTAR

1" MIN.

VENT @ 24" O/C

INSULATION  
RETAINER

ADJUSTABLE  
WALL TIE

GYPSUM WALLBOARD,  
METAL FURRING  
(OPTIONAL),  
CONCRETE MASONRY  
UNIT (CMU),  
AIR/VAPOR BARRIER  
MEMBRANE,  
RIGID OR SEMI-RIGID  
INSULATION (THICKNESS  
DEPENDANT ON  
REQUIRED R-VALUE),  
MIN. 1" AIR SPACE,  
ADAIR® LIMESTONE  
MASONRY UNIT.



**ARRISCRAFT**  
INTERNATIONAL  
BUILDING STONE • BRICK • LIMESTONE

**ARRISCRAFT • CADD**

TITLE:  
**EIFS/CALCIUM SILICATE  
TRANSITION (BULLNOSE)**

DATE DRAWN:  
08/30/04

SCALE:  
3"=1'-0"

DRAWN BY:  
LPS

DETAIL No:  
CBI AD12S

**U103**