



SUBSTRATE
 EIFS WITH
 DRAINAGE BOARD/
 STUCCO
 PREFINISHED METAL
 DRIP FLASHING
 BACKER ROD
 AND SEALANT
 SLOPED WATERTABLE
 CALCIUM SILICATE
 MASONRY UNIT (CSMU)
 RAKE BACK MORTAR
 BETWEEN UNITS APPROX.
 1" DEEP. COVER WITH
 BACKER ROD AND SEALANT
 TO PROTECT MORTAR

HORIZONTAL
 REINFORCING
 WHEN REQUIRED

1" MIN.
 1-1/2" MIN.

VENT @ 24" O/C

MASONRY TIE OR
 MECHANICAL ANCHOR
 IN HEAD JOINT

INSULATION
 RETAINER

ADJUSTABLE
 WALL TIE

GYPSUM WALLBOARD,
 METAL FURRING
 (OPTIONAL),
 CONCRETE MASONRY
 UNIT (CMU),
 AIR/VAPOR BARRIER
 MEMBRANE,
 RIGID OR SEMI-RIGID
 INSULATION (THICKNESS
 DEPENDANT ON
 REQUIRED R-VALUE),
 MIN. 1" AIR SPACE,
 ADAIR® LIMESTONE
 MASONRY UNIT.



ARRISCRAFT
 INTERNATIONAL
 BUILDING STONE • BRICK • LIMESTONE

ARRISCRAFT • CADD

TITLE:
 EIFS/CALCIUM SILICATE
 TRANSITION (WATERTABLE)

DATE DRAWN:
 08/30/04

SCALE:
 3"=1'-0"

DRAWN BY:
 LPS

DETAIL No:
 CBI AD12S

U104