



ADJUSTABLE WALL TIE  
INSULATION RETAINER

HORIZONTAL REINFORCING  
WHEN REQUIRED

MORTAR DROP CONTROL

FLASHING MEMBRANE SURFACE  
ADHERE TO SUBSTRATE

UNOBSTRUCTED  
WEEP SYSTEM @ 600 MM O/C

PREFINISHED METAL DRIP EDGE  
SET ON TWO BEADS OF SEALANT

10 MIN.

HIGH SLUMP  
MASONRY GROUT

DRAINAGE TILE

GYPSUM WALLBOARD,  
METAL FURRING  
(OPTIONAL),  
CONCRETE MASONRY  
UNIT (CMU),  
AIR/VAPOUR BARRIER  
MEMBRANE,  
RIGID OR SEMI-RIGID  
INSULATION (THICKNESS  
DEPENDANT ON  
REQUIRED R-VALUE),  
MIN. 25 MM AIR SPACE,  
CALCIUM SILICATE  
BUILDING STONE.

VERTICAL REINFORCING  
IF REQUIRED

FLOOR BY OTHER

AIR/VAPOUR BARRIER

BUILDING PAPER

GRAVEL MOWING  
STRIP



**ARRISCRAFT • CADD**

TITLE: FOUNDATION WALL/  
BURIED MASONRY UNIT  
(GRAVEL MOWING STRIP AND FRENCH DRAIN)

DATE DRAWN:  
08/30/04

SCALE:  
1:5

DRAWN BY:  
LPS

DETAIL No:  
CB SH3M

**D004**