



ADJUSTABLE WALL TIE
INSULATION RETAINER

MORTAR DROP CONTROL
FLASHING MEMBRANE SURFACE ADHERE TO SUBSTRATE

UNOBSTRUCTED WEEP SYSTEM @ 600 MM O/C

PREFINISHED METAL DRIP EDGE SET ON TWO BEADS OF SEALANT

ADAIR® LIMESTONE MARBLE BASE COURSE

150 MIN.

10 MIN.
COMPRESSIBLE BACKER ROD AND SEALANT
PREMOULDED EXPANSION JOINT FILLER
2% SLOPE MIN.

GYPSUM WALLBOARD,
METAL FURRING (OPTIONAL),
CONCRETE MASONRY UNIT (CMU),
AIR/VAPOUR BARRIER MEMBRANE,
RIGID OR SEMI-RIGID INSULATION (THICKNESS DEPENDANT ON REQUIRED R-VALUE),
MIN. 25 MM AIR SPACE,
CALCIUM SILICATE BUILDING STONE.

HORIZONTAL REINFORCING WHEN REQUIRED

VERTICAL REINFORCING IF REQUIRED

FLOOR BY OTHER

AIR/VAPOUR BARRIER
BUILDING PAPER
HIGH SLUMP MASONRY GROUT



ARRISCRAFT • CADD

TITLE: FOUNDATION WALL/
BURIED MASONRY UNIT
(ADAIR® LIMESTONE BASE COURSE)

DATE DRAWN:
08/30/04

SCALE:
1:5

DRAWN BY:
LPS

DETAIL No:
CB SH3M
D006