



CALCIUM SILICATE BUILDING STONE, MIN. 25 MM AIR SPACE, RIGID OR SEMI-RIGID INSULATION (THICKNESS DEPENDANT ON REQUIRED R-VALUE), AIR/VAPOUR BARRIER MEMBRANE, CONCRETE MASONRY UNIT (CMU), METAL FURRING (OPTIONAL), GYPSUM WALLBOARD.

FLASHING MEMBRANE SURFACE ADHERE TO SUBSTRATE

MORTAR DROP CONTROL

CORROSION PROTECTED CONTINUOUS STEEL ANGLE AND STEEL BRACKET

UNOBSTRUCTED WEEP SYSTEM @ 600 MM O/C

PREFINISHED METAL DRIP EDGE SET ON TWO BEADS OF SEALANT

HORIZONTAL REINFORCING WHEN REQUIRED

VERTICAL REINFORCING IF REQUIRED

FLOOR BY OTHER

150 MIN.
10 MIN.
PARGING
COMPRESSIBLE BACKER ROD AND SEALANT
PREMOULDED EXPANSION JOINT FILLER
2% SLOPE MIN.

WELD PLATE CAST IN PLACE
AIR/VAPOUR BARRIER
BUILDING PAPER
STEEL STUD FURRING WITH INSULATION



ARRISCRAFT • CADD
 TITLE:
 ALTERNATIVE FOUNDATION TO WALL
 (SHELF ANGLE)

DATE DRAWN:
08/30/04
 SCALE:
1:5
 DRAWN BY:
LPS

DETAIL No:
CB SH3M
D008