



MECHANICAL ANCHOR

10
1

RAKE BACK MORTAR BETWEEN UNITS APPROX. 1" DEEP COVER WITH BACKER ROD AND SEALANT TO PROTECT MORTAR

STONE OR PRECAST CAP

1" MIN.
1-1/2" MIN.

1" MIN.
1-1/2" MIN.

FLEXIBLE FLASHING MEMBRANE BELOW STONE OR PRECAST CAP

VERTICAL REINFORCING WHEN REQUIRED

COVERBOARD

ROOF BY OTHER

VENT @ 24" O/C
CALCIUM SILICATE MASONRY UNIT (CSMU), MIN. 1" AIR SPACE, RIGID OR SEMI-RIGID INSULATION (THICKNESS DEPENDANT ON REQUIRED R-VALUE), AIRVAPOR BARRIER MEMBRANE, CONCRETE MASONRY UNIT (CMU).

FLASHING MEMBRANE SURFACE ADHERE TO SUBSTRATE

MORTAR DROP CONTROL

WELD PLATE CAST IN PLACE

CORROSION PROTECTED CONTINUOUS STEEL ANGLE AND STEEL BRACKET

UNOBSTRUCTED WEEP SYSTEM @ 24" O/C

3/8" MIN.

COMPRESSIBLE BACKER ROD AND SEALANT

LONG LEG OUTER TRACK ANCHORED TO SLAB, NEITHER SHEATHING OR DRYWALL ATTACHED TO ALLOW FOR DEFLECTION OF SLAB



ARRISCRAFT
INTERNATIONAL
BUILDING STONE • BRICK • LIMESTONE

ARRISCRAFT • CADD

TITLE:

ALTERNATIVE PARAPET TO WALL WITH STONE OR PRECAST CAP

DATE DRAWN:
08/30/04

SCALE:
3"=1'-0"

DRAWN BY:
LPS

DETAIL No:

SS 04R

U125