



ADJUSTABLE WALL TIE

INSULATION RETAINER

FLASHING MEMBRANE
SURFACE ADHERE
TO SUBSTRATE

MORTAR DROP
CONTROL

UNOBSTRUCTED
WEEP SYSTEM
@ 24" O/C

PREFINISHED
METAL DRIP EDGE
SET ON TWO BEADS
OF SEALANT
3/8 MIN.

CORROSION PROTECTED
CONTINUOUS STEEL
ANGLE AND STEEL BRACKET
6" MIN.

PARKING

GYPSUM WALLBOARD
STEEL STUD WALL,
EXTERIOR SHEATHING,
AIR/VAPOR BARRIER
MEMBRANE,
RIGID OR SEMI-RIGID
INSULATION (THICKNESS
DEPENDANT ON
REQUIRED R-VALUE),
MIN. 1" AIR SPACE,
CALCIUM SILICATE
MASONRY UNIT (CSMU).

STEEL TRACK FASTENER
(SCREW SIZE IS
DETERMINED BY
LOAD SUPPORTED)

STEEL TRACK

WELD PLATE
CAST IN PLACE

AIR/VAPOR
BARRIER

BUILDING PAPER

STEEL STUD
FURRING WITH
INSULATION



ARRISCRAFT
INTERNATIONAL
BUILDING STONE • BRICK • LIMESTONE

ARRISCRAFT • CADD

TITLE:

ALTERNATIVE FOUNDATION TO WALL
(SHELF ANGLE) WITH SOIL

DATE DRAWN:

08/30/04

SCALE:

3"=1'-0"

DRAWN BY:

LPS

DETAIL No:

SS 04S

U008