



MECHANICAL ANCHOR

10
1

RAKE BACK MORTAR
BETWEEN UNITS
APPROX. 1" DEEP
COVER WITH
BACKER ROD AND
SEALANT TO
PROTECT MORTAR

STONE OR
PRECAST CAP

1" MIN.
1-1/2" MIN.

1" MIN.
1-1/2" MIN.

VENT @ 24" O/C

FLEXIBLE FLASHING
MEMBRANE BELOW
STONE OR PRECAST
CAP

CALCIUM SILICATE
MASONRY UNIT (CSMU),
MIN. 1" AIR SPACE,
RIGID OR SEMI-RIGID
INSULATION (THICKNESS
DEPENDANT ON
REQUIRED R-VALUE),
AIR/VAPOR BARRIER
MEMBRANE,
CONCRETE MASONRY
UNIT (CMU).

VERTICAL
REINFORCING
WHEN REQUIRED

FLASHING MEMBRANE
SURFACE ADHERE
TO SUBSTRATE

COVERBOARD

ROOF BY OTHER

MORTAR DROP
CONTROL

WELD PLATE
CAST IN PLACE

CORROSION PROTECTED
CONTINUOUS STEEL
ANGLE AND STEEL BRACKET

UNOBSTRUCTED
WEEP SYSTEM @ 24" O/C

3/8" MIN.

COMPRESSIBLE
BACKER ROD
AND SEALANT

LONG LEG OUTER
TRACK ANCHORED TO
SLAB, NEITHER SHEATHING
OR DRYWALL ATTACHED TO
ALLOW FOR DEFLECTION
OF SLAB



ARRISCRAFT
INTERNATIONAL
BUILDING STONE • BRICK • LIMESTONE

ARRISCRAFT • CADD

TITLE:

ALTERNATIVE PARAPET TO WALL
WITH STONE OR PRECAST CAP

DATE DRAWN:
08/30/04

SCALE:
3"=1'-0"

DRAWN BY:
LPS

DETAIL No:

SS 04S

U125