



GYPSUM WALLBOARD,
 STEEL STUD WALL,
 EXTERIOR SHEATHING,
 AIR/VAPOR BARRIER MEMBRANE,
 16 GAUGE Z-CHANNEL,
 RIGID OR SEMI RIGID INSULATION
 (THICKNESS DEPENDANT ON
 REQUIRED R-VALUE),
 ALUMINUM CHANNELS,
 1" AIR SPACE,
 CALCIUM SILICATE CLIP UNIT

Z-CHANNEL FASTENERS @ 16" O.C.
 C/W SHIMS AS REQUIRED, MAX.
 SHIMS 3/4" THICK

STEEL TRACK
 SILL FLASHING

REQUIRED SHIM TO
 SEPARATE
 ALUMINUM CHANNEL
 FROM Z-CHANNEL, MAX.
 SHIMS 3/4" THICK

BACKER ROD AND
 SEALANT

FLASHING MEMBRANE
 ADHERED TO SUBSTRATE

PRE-FINISHED METAL
 DRIP EDGE

PARKING
 6" MIN.

2% SLOPE
 MIN.



ARRISCRAFT
 INTERNATIONAL
 BUILDING STONE • BRICK • LIMESTONE

ARRISCRAFT • CADD

TITLE:
 ALTERNATE FOUNDATION WALL
 JUNCTION WITH SOIL

DATE DRAWN:
 01/15/12

SCALE:
 3"=1'-0"

DRAWN BY:
 D.D.N.

DETAIL No:
 SS 08RU

AC008