

**NOTE: REFER TO**  
**DOOR JAMB: SS08RUAC070**  
**DOOR THRESHOLD: SS08RUAC050**

BACKER ROD AND SEALANT  
 REQUIRED SHIM TO SEPARATE ALUMINUM CHANNEL FROM Z-CHANNEL, MAX. SHIMS 3/4" THICK  
 FLASHING MEMBRANE ADHERED TO SUBSTRATE

GYPSUM WALLBOARD,  
 STEEL STUD WALL,  
 EXTERIOR SHEATHING,  
 AIR/VAPOR BARRIER MEMBRANE,  
 16 GAUGE Z-CHANNEL,  
 RIGID OR SEMI RIGID INSULATION  
 (THICKNESS DEPENDANT ON  
 REQUIRED R-VALUE),  
 ALUMINUM CHANNELS,  
 1" AIR SPACE,  
 CALCIUM SILICATE CLIP UNIT

COMPRESSIBLE BACKER ROD AND SEALANT  
 UNOBSTRUCTED WEEP SYSTEM @ 24" O/C  
 PREFINISHED METAL DRIP EDGE

Z-CHANNEL FASTENERS @ 16" O.C. C/W SHIMS AS REQUIRED, MAX. SHIMS 3/4" THICK

WOOD BLOCKING

COMPRESSIBLE BACKER ROD AND SEALANT ALL AROUND THE FRAME

SPRAY APPLIED FOAM INSULATING AIR SEAL ALL AROUND FRAME

PREMANUFACTURED THERMALLY BROKEN ALUMINUM DOOR ASSEMBLY

1 1/8"



**ARRISCRAFT**  
 INTERNATIONAL  
 BUILDING STONE • BRICK • LIMESTONE

**ARRISCRAFT • CADD**

TITLE:

ALUMINUM DOOR HEAD

DATE DRAWN:  
01/15/12

SCALE:  
3"=1'-0"

DRAWN BY:  
D.D.N.

DETAIL No:

SS 08RU

**AC060**