



BACKER ROD AND SEALANT

BULLNOSE WATERTABLE CALCIUM SILICATE CLIP UNIT

FLASHING MEMBRANE ADHERED TO SUBSTRATE

REQUIRED SHIM TO SEPARATE ALUMINUM CHANNEL FROM Z-CHANNEL, MAX. SHIMS 3/4" THICK

BACKER ROD AND SEALANT

Z-CHANNEL FASTENERS @ 16" O.C. CW SHIMS AS REQUIRED, MAX. SHIMS 3/4" THICK

GYPSUM WALLBOARD, STEEL STUD WALL, EXTERIOR SHEATHING, AIR/VAPOR BARRIER MEMBRANE, 16 GAUGE Z-CHANNEL, RIGID OR SEMI RIGID INSULATION (THICKNESS DEPENDANT ON REQUIRED R-VALUE), ALUMINUM CHANNELS, 1" AIR SPACE, CALCIUM SILICATE CLIP UNIT



ARRISCRAFT
INTERNATIONAL
BUILDING STONE • BRICK • LIMESTONE

ARRISCRAFT • CADD

TITLE:

BULLNOSE WATERTABLE

DATE DRAWN:
01/15/12

SCALE:
3"=1'-0"

DRAWN BY:
D.D.N.

DETAIL No:
SS 08RU

AC100