



ATTACH SHEATHING WITH APPROVED SCREWS (TYPICAL @ EVERY STUD)

POINTING MORTAR

ATTACH CEMENT BOARD WITH APPROVED SCREWS (TYPICAL @ EVERY STUD)

CONTINUOUS VERTICAL JOINT FILLED WITH BACKER ROD AND SEALANT

3/8" MIN.

GYPSUM WALLBOARD,  
 VAPOR BARRIER (LOCATION DEPENDENT ON CLIMATE ZONE),  
 STEEL STUD WALL,  
 BATT INSULATION (THICKNESS DEPENDENT ON REQUIRED R-VALUE),  
 EXTERIOR SHEATHING,  
 CEMENT BOARD,  
 LATICRETE AIR & WATER BARRIER,  
 HI-BOND MASONRY VENEER MORTAR - POLYMER FORTIFIED,  
 CALCIUM SILICATE TILE UNIT

**Arriscraft**  
 Building Stone · Brick · Limestone

**ARRISCRAFT-CADD**

DETAIL No:

SS08RAT

TITLE:

OUTSIDE QUIRK  
 MITERED CORNER

**U150**

DATE DRAWN:  
 03/02/15

SCALE:  
 3"=1'-0"

DRAWN BY:  
 TRI