



ADJUSTABLE WALL TIE
 INSULATION RETAINER

FLASHING MEMBRANE
 SURFACE ADHERE
 TO SUBSTRATE

MORTAR DROP
 CONTROL

UNOBSTRUCTED
 WEEP SYSTEM @ 24" O/C

PREFINISHED
 METAL DRIP EDGE
 SET ON TWO
 BEADS OF SEALANT

CORROSION PROTECTED
 STEEL ANGLE LINTEL

COMPRESSIBLE BACKER
 ROD AND SEALANT

PREMANUFACTURED
 THERMALLY BROKEN
 ALUMINUM
 WINDOW ASSEMBLY

GYPSUM WALLBOARD
 STEEL STUD WALL,
 EXTERIOR SHEATHING,
 AIR/VAPOR BARRIER
 MEMBRANE,
 RIGID OR SEMI-RIGID
 INSULATION (THICKNESS
 DEPENDANT ON
 REQUIRED R-VALUE),
 MIN. 1" AIR SPACE,
 CALCIUM SILICATE MASONRY
 UNIT (CSMU).

WOOD BLOCKING

COMPRESSIBLE
 BACKER ROD AND
 SEALANT ALL
 AROUND THE FRAME

SPRAY APPLIED FOAM
 INSULATING AIR SEAL
 ALL AROUND FRAME



ARRISCRAFT
 INTERNATIONAL
 BUILDING STONE • BRICK • LIMESTONE

ARRISCRAFT • CADD

TITLE:
**ALUMINUM WINDOW
 HEAD**

DATE DRAWN:
 08/30/04

SCALE:
 3"=1'-0"

DRAWN BY:
 LPS

DETAIL No:
 SS 08R

U030