



ADJUSTABLE WALL TIE
INSULATION RETAINER

GYPSUM WALLBOARD
STEEL STUD WALL,
EXTERIOR SHEATHING,
AIR/VAPOR BARRIER
MEMBRANE,
RIGID OR SEMI-RIGID
INSULATION (THICKNESS
DEPENDANT ON
REQUIRED R-VALUE),
MIN. 1" AIR SPACE,
CALCIUM SILICATE MASONRY
UNIT (CSMU).

FLASHING MEMBRANE
SURFACE ADHERE
TO SUBSTRATE

WOOD BLOCKING

MORTAR DROP
CONTROL

UNOBSTRUCTED
WEEP SYSTEM @ 24" O/C

CORROSION PROTECTED
STEEL ANGLE LINTEL

COMPRESSIBLE
BACKER ROD AND
SEALANT ALL
AROUND THE FRAME

COMPRESSIBLE BACKER
ROD AND SEALANT

SPRAY APPLIED FOAM
INSULATING AIR SEAL
ALL AROUND FRAME

PREMANUFACTURED
THERMALLY BROKEN
ALUMINUM
DOOR ASSEMBLY



ARRISCRAFT
INTERNATIONAL
BUILDING STONE • BRICK • LIMESTONE

ARRISCRAFT • CADD

TITLE:
**ALTERNATIVE ALUMINUM
DOOR HEAD**

DATE DRAWN:
08/30/04

SCALE:
3"=1'-0"

DRAWN BY:
LPS

DETAIL No:
SS 08R

U061