



WOOD BLOCKING

BACKER ROD AND SEALANT

VENT @ 24" O/C

MORTAR DROP CONTROL

FLASHING MEMBRANE SURFACE ADHERE TO SUBSTRATE

UNOBSTRUCTED WEEP SYSTEM @ 24" O/C

PREFINISHED METAL DRIP EDGE SET ON TWO BEADS OF SEALANT

CORROSION PROTECTED CONTINUOUS STEEL ANGLE AND STEEL BRACKET

COMPRESSIBLE BACKER ROD AND SEALANT

CALCIUM SILICATE MASONRY UNIT (CSMU), MIN. 1" AIR SPACE, RIGID OR SEMI-RIGID INSULATION (THICKNESS DEPENDANT ON REQUIRED R-VALUE), AIR/VAPOR BARRIER MEMBRANE, EXTERIOR SHEATHING, STEED STUD WALL, GYPSUM WALLBOARD.

METAL CAP FLASHING

FLEXIBLE FLASHING MEMBRANE BELOW METAL CAP

COVERBOARD

CONTINUOUS BENT STEEL PARAPET SUPPORT

ROOF BY OTHER

WELD PLATE CAST IN PLACE

LONG LEG OUTER TRACK ANCHORED TO SLAB, NEITHER SHEATHING OR DRYWALL ATTACHED TO ALLOW FOR DEFLECTION OF SLAB



**ARRISCRAFT**  
INTERNATIONAL  
BUILDING STONE • BRICK • LIMESTONE

**ARRISCRAFT • CADD**

TITLE:

LOW PARAPET TO WALL  
WITH METAL CAP FLASHING

DATE DRAWN:  
08/30/04

SCALE:  
3"=1'-0"

DRAWN BY:  
LPS

DETAIL No:

SS 08R

**U120**