



**NOTE:** REFER TO  
 DOOR HEAD: SS08SUAC060  
 DOOR THRESHOLD: SS08SUAC050

REQUIRED SHIM TO SEPARATE ALUMINUM CHANNEL FROM Z-CHANNEL, MAX. SHIMS 3/4" THICK

BACKER ROD AND SEALANT

GYPSUM WALLBOARD,  
 STEEL STUD WALL,  
 EXTERIOR SHEATHING,  
 AIR/VAPOR BARRIER MEMBRANE,  
 16 GAUGE Z-CHANNEL,  
 RIGID OR SEMI RIGID INSULATION  
 (THICKNESS DEPENDANT ON  
 REQUIRED R-VALUE),  
 ALUMINUM CHANNELS,  
 1" AIR SPACE,  
 CALCIUM SILICATE CLIP UNIT

Z-CHANNEL FASTENERS @ 16" O.C. C/W SHIMS AS REQUIRED, MAX. SHIMS 3/4" THICK

WOOD BLOCKING

FINISHED END CALCIUM SILICATE CLIP UNIT

COMPRESSIBLE BACKER ROD AND SEALANT ALL AROUND THE FRAME

PREMANUFACTURED THERMALLY BROKEN ALUMINUM DOOR ASSEMBLY

SPRAY APPLIED FOAM INSULATING AIR SEAL ALL AROUND FRAME



**ARRISCRAFT**  
 INTERNATIONAL  
 BUILDING STONE • BRICK • LIMESTONE

**ARRISCRAFT • CADD**

TITLE: ALUMINUM DOOR JAMB (PLAN VIEW)

DATE DRAWN: 01/15/12

SCALE: 3"=1'-0"

DRAWN BY: D.D.N.

DETAIL No: SS 08SU

**AC070**