



**ARCHITECT NOTE:**

- DETAIL FOR UNSUPPORTED PROGUARD DP® - DOUBLE DRAINAGE PLANE PANELS.
- ENGINEER OF RECORD TO SELECT PROGUARD DP® SCREW SPACING USING NTA REPORT TRIG030116-28.

INSULATION CHAMFERED AT TOP AND BOTTOM OF PANEL EDGES TO ALLOW FOR CONTINUOUS DRAINAGE

1'-0" x 8'-0" PROGUARD DP® BASE WEEP PANEL - DOUBLE DRAINAGE PLANE AT ALL FLASHING LOCATIONS

STEEL TRACK FASTENER (SCREW SIZE IS DETERMINED BY LOAD SUPPORTED)

STEEL TRACK

FLASHING MEMBRANE ADHERED MIN. 4" UP SUBSTRATE. OVERLAP AIR / WATER BARRIER OVER FLASHING

ATTACH PROGUARD DP® PANELS WITH SILVER C APPROVED SCREWS THROUGH TO STUDS (TYPICAL)

TAPE JOINT WITH ALKALI-RESISTANT MESH TAPE AND MUD JOINT WITH MVIS™ HI-BOND VENEER MORTAR  
MVIS™ POINTING MORTAR

COMPRESSIBLE BACKER ROD AND SILICONE SEALANT w/ WEEP HOLES @ 8" o.c.  
PREFINISHED METAL DRIP EDGE SET ON TWO BEADS OF URETHANE SEALANT

COMPRESSIBLE BACKER ROD AND SILICONE SEALANT

PREMOLDED EXPANSION JOINT FILLER

PARGING

BUILDING PAPER

AIR / VAPOR BARRIER



**ARRISCRAFT-CADD**

DETAIL No:  
SS08SAT - DP2U

TITLE:  
**ALTERNATIVE FOUNDATION TO WALL JUNCTION WITH PAVING**

**U003**

DATE DRAWN: 16 Jan 2021	SCALE: 3"=1'-0"	DRAWN BY: TRI
----------------------------	--------------------	------------------